

solar electricity

245 WATT

MULTI-PURPOSE MODULE

NEC 2008 Compliant New Triple Tab Technology



NU-U245P1

MULTI-PURPOSE 245 WATT MODULE FROM THE WORLD'S TRUSTED SOURCE FOR SOLAR.

Using breakthrough technology, made possible by nearly 50 years of proprietary research and development, Sharp's NU-U245P1 solar module incorporates an advanced cell surface texturing process to increase light absorption and improve efficiency. Common applications include commercial and residential grid-tied roof systems as well as ground mounted arrays. Designed to withstand rigorous operating conditions, this module offers high power output per square foot of solar array.

Sharp's most powerful commercial module manufactured today.

ENGINEERING EXCELLENCE

High module efficiency for an outstanding balance of size and weight to power and performance.

DURABLE

Tempered glass, EVA lamination and weatherproof backskin provide long-life and enhanced cell performance.

RELIABLE

25-year limited warranty on power output.

HIGH PERFORMANCE


This module uses an advanced solar cell surface texturing process to increase light absorption and improve efficiency.

INNOVATIVE

156 mm pseudo-square monocrystalline solar cells provide high power output. Ideal for large commercial rooftops where space is a premium.



The NU-U245P1 offers industry-leading performance for a variety of applications.



Improved Frame Technology

SHARP: THE NAME TO TRUST

When you choose Sharp, you get more than well-engineered products. You also get Sharp's proven reliability, outstanding customer service and the assurance of our 25-year limited warranty on power output. A global leader in solar electricity, Sharp powers more homes and businesses than any other solar manufacturer worldwide.

245 WATT

NU-U245P1

NEC 2008 Compliant

Module output cables: 12 AWG with locking connectors

ELECTRICAL CHARACTERISTICS		
Maximum Power (Pmax)*	245 W	
Tolerance of Pmax	+10%/-5%	
Type of Cell	Monocrystalline silicon	
Cell Configuration	60 in series	
Open Circuit Voltage (Voc)	37.3 V	
Maximum Power Voltage (Vpm)	30.4 V	
Short Circuit Current (Isc)	8.7 A	
Maximum Power Current (Ipm)	8.08 A	
Module Efficiency (%)	15.0%	
Maximum System (DC) Voltage	600 V	
Series Fuse Rating	15 A	
NOCT	47.5°C	
Temperature Coefficient (Pmax)	-0.485%/°C	
Temperature Coefficient (Voc)	-0.351%/°C	
Temperature Coefficient (Isc)	0.053%/°C	

^{*}Illumination of 1 kW/m² (1 sun) at spectral distribution of AM 1.5 (ASTM E892 global spectral irradiance) at a cell temperature of 25°C.

MECHANICAL CHARACTERISTICS		
Dimensions (A x B x C below)	39.1" x 64.6" x 1.8"/994 x 1640 x 46 mm	
Cable Length (I)	43.3"/1100 mm	
Output Interconnect Cable**	12 AWG with MC4 Locking Connector	
Weight	44.1 lbs / 20.0 kg	
Max Load	50 psf (2400 Pascals)	
Operating Temperature (cell)	-40 to 194°F / -40 to 90°C	

^{**}A safety lock clip (Multi Contact part number PV-SSH4) may be required in readily accessible locations per NEC 2008 690.33 (C)


QUALIFICATIONS		
UL Listed	UL 1703	c (UL) us
Fire Rating	Class C	c QL) us

WARRANTY

25-year limited warranty on power output Contact Sharp for complete warranty information

Design and specifications are subject to change without notice. Sharp is a registered trademark of Sharp Corporation. All other trademarks are property of their respective owners. Contact Sharp to obtain the latest product manuals before using any Sharp device. Cover photo: Solar Installation by SPG Solar.





Contact Sharp for tolerance specifications

"BUY AMERICAN"

Sharp solar modules are manufactured in the United States and Japan, and qualify as "American" goods under the "Buy American" clause of the American Recovery and Reinvestment Act (ARRA).



SHARP ELECTRONICS CORPORATION 5901 Bolsa Avenue, Huntington Beach, CA 92647 1-800-SOLAR-06 • Email: sharpsolar@sharpusa.comwww.sharpusa.com/solar



